

# Natural sand replacement in concrete

M. Pilegis\*, D.R. Gardner and R.J. Lark,

Cardiff University

**Prof. Bob Lark**, Professor, Cardiff University lark@cf.ac.uk

Professor Bob Lark is a Chartered Engineer with over 30 years of varied Civil Engineering experience. He has been an academic at Cardiff University for 15 years and during this time has undertaken research on the design and behaviour of concrete and steel structures, bridge monitoring and assessment, and the development of life cycle analysis and asset management techniques. He has solely and jointly generated research income in excess of £1M. He has supervised 10 successful PhDs and is currently jointly supervising a further 4 PhD students and a Research Associate. He has over 60 publications in international journals and refereed conferences since 1996.

**Dr Diane Gardner**, Lecturer, Cardiff University gardnerdr@cf.ac.uk

Dr Gardner graduated from Cardiff with a 1st class MEng degree in Civil Engineering in 2002. Following this she undertook a PhD in experimental and numerical studies of the permeability of concrete. She obtained PhD in 2005 and joined Hyder Consulting UK Ltd, and spent 3 years working in their bridge/civil structures team. She took up her present academic post in January 2009 and her primary research interests are in experimental testing of sustainable cementitious materials.

**Martins Pilegis**, PhD student, Cardiff University PilegisM@cf.ac.uk

Martins Pilegis graduated Cardiff University with a 1st class BEng degree in Civil Engineering in 2010. Currently he is a research student at the Cardiff School of Engineering, Cardiff University.

\*corresponding author

**Keywords:** manufactured sand, concrete, sand replacement, workability, strength

## Introduction

The Welsh Assembly government has identified a need for an effective method for dealing with the growing stockpiles of waste crusher dust in local quarries. The current practice in the UK is to stockpile the excess crusher dust or blend it with natural sand to produce an acceptable particle size distribution for use in concrete, but the production rate of the surplus quarry fines surpasses the rate at which they can be used due to the high percentage of blending required to produce concrete with acceptable properties [1].

A research project was commissioned to investigate the feasibility of manufacturing sand from the waste quarry fines that could be used to fully replace natural sand and sand blends in concrete applications. This was done in collaboration with Kayasand, a company which offers a dry sand manufacturing process (V7 process) which improves the shape of sand particles and controls the grading [2].

In this study manufactured sands produced with the V7 process from four quarries were considered. The resulting consistency and compressive strength of concrete when sands were used as 100% replacement for natural sand is presented.

## Materials

In the study the following materials were used: CEM I 52.5 N conforming to EN 197-1, sea dredged natural sand from Bristol channel conforming to BS EN 12620:2002, 4/20 mm crushed limestone coarse aggregate, and sands produced from quarry dusts using the V7 dry manufacturing system.

## Notation

Sands were manufactured from basalt, granite, limestone and sandstone quarry dusts yielding at least four gradings for each sand. These gradings differed mainly in the sub 63 micron particle or fines content. The designation for the materials used in this paper is shown in Table 1.

Table 1 Notation of materials used in the study

Material	Designation	% fines	Material	Designation	% fines
Natural Sand	NS	-	Granite crusher dust	G-Dust	-
Coarse aggregate	CA	-	Granite sands	G-A	2
Basalt crusher dust	B-Dust	-		G-B	2.9
Basalt sands	B-A	1		G-C	5.1
	B-B	2.9		G-D	6.5
	B-C	5.1		G-E	9
	B-D	7.4	Sandstone crusher dust	S-Dust	-
Limestone crusher dust	L-Dust	-	Sandstone sands	S-A	3.5
Limestone sands	L-A	2.8		S-B	5
	L-B	4.9		S-C	7
	L-C	7.1		S-D	9
	L-D	9			

## Experimental programme

### Fine aggregate tests

All sands were tested for particle size distribution according to BS EN 933-1, Particle density and water absorption according to BS EN 1097-6, Methylene blue test (MBV) according to BS EN 933-9 on the 0/2mm fraction, Sand equivalence test (SE) according to BS EN 933-8 on the 0/2mm fraction and using the New Zealand Flow cone (NZFC) according to NZS 3111-1986. Test results are shown in Figures 1-6 and Table 2.

### Concrete tests

Fresh concrete was tested for slump according to BS EN 12350-2:2009, air entrainment and plastic density. Hardened concrete specimens were tested for compressive strength at 1, 7 and 28 days and flexural strength at 28 days.

### Concrete mixtures

Concrete mixes were made from all sands using the mix composition reported in Table 2 with the aim of achieving an S2 (50- 90 mm) slump and using the concrete mix containing natural sand as the control. For each sand the water to cement ratio was adjusted in order to achieve an S2 slump in the –B graded sand mix. This water to cement ratio was then kept constant for the remainder of the mixes of the same sand mineralogy and the change in slump recorded.

All mix proportioning took into account the water content and absorption capacity of the coarse and fine aggregates. Nine 100 mm cubes and three 100x100x500 mm beams were made from every mix and tested at the corresponding age.

Table 2 Concrete mix composition

Cement	Coarse aggregate	Fine aggregate	Water/cement ratio
350 kg/m <sup>3</sup>	1040 kg/m <sup>3</sup>	753 kg/m <sup>3</sup>	varies

## Results and discussion

The results from the fine aggregate, fresh concrete and hardened concrete tests are presented in the following sections. The results of the crusher dust (using the 0-4mm fraction) have been included for completeness although it is recognised that a mix comprising 100% crusher dust as a replacement for natural sand in concrete is unrealistic. However, the crusher dust results do provide a useful indication of the success of the sand manufacturing process through the sand characterisation and the fresh concrete workability results.

### Fine aggregate test results

Figures 1-4 show the particle size distributions for manufactured sands and the corresponding crusher dust 0-4 mm fractions used in the sand production. It can be seen that all manufactured sands irrespective of the parent material, yield similar particle size distributions

with a sub 63 micron particle content ranging from 1 – 9 %. Furthermore, higher fines gradings contain more 0.3 to 1 mm particles than the feed crusher dust fractions as indicated by the steeper gradients of the particle size distribution curves in that region. The 0.3 – 1 mm fraction usually is deemed to be deficient in crusher dusts, therefore requiring a blend with natural sand to comply with standards and perform adequately in concrete mixtures [1].




Figure 1 Sandstone sand particle size distributions




Figure 2 Basalt sand particle size distributions




Figure 3 Granite sand particle size distributions




Figure 4 Limestone sand particle size distributions




Figure 5 Natural sand and coarse aggregate particle size distributions

Table 3 shows the methylene blue value, sand equivalence and water absorption test results. Dredged natural sand has the lowest MBV and the highest SE value indicating a clean sand

without deleterious particles. Such results were to be expected as natural sand from a dredged source typically has less than 1% fines as a result of additional fines being washed out in the screening process.

Table 3 Fine aggregate characterisation test results

Sample	MBV, g of MB solution per kg of 0/2mm sand	SE	WA <sub>24</sub> , %
NS	0.24	94	1.04
G-Dust	0.77	50	0.58
G-A	0.39	80	0.58
G-B	0.40	74	
G-C	0.47	71	
G-D	0.50	70	
G-E	0.63	69	
B-Dust	5.36	48	1.92
B-A	2.10	73	1.67
B-B	2.29	61	
B-C	2.64	60	
B-D	2.90	58	
L-Dust	0.40	65	0.62
L-A	0.47	72	0.45
L-B	0.40	71	
L-C	0.40	71	
L-D	0.37	67	
S-Dust	3.19	27	1.53
S-A	1.40	31	0.98
S-B	1.48	30	
S-C	1.50	28	
S-D	1.63	27	

The low MBV values for granite and limestone sands indicate that the fines are mostly dust of fracture created during the processing. As such a good performance was expected and confirmed in the concrete trials discussed in the next section.

The high MBV (>1) and low SE (<70) for the sandstone and basalt sands indicate the potential presence of clays which increased the water demand of the concrete mixes as shown by the concrete trial results in Table 4.

It can be seen that all crusher dusts have higher MBV and lower SE values than manufactured sands indicating that the V7's grading and air screening process has removed some fines and



values are higher than the expected trend. This might be attributed to optimum packing and the lubricating effect of the fines offsetting the negative effect of the increased specific surface area.

Table 4 Concrete mixture results

Mix	w/c ratio	Slump, mm	Compressive strength, N/mm <sup>2</sup>			Flexural strength N/mm <sup>2</sup>
			1 day	7 day	28 day	28day
NS	0.48	95	23.8	48.0	58.9	6.1
G-Dust	0.66	80	12.5	30.3	39.1	-
G-A	0.58	120	17.6	43.5	52.2	5.6
G-B	0.58	80	17.0	40.2	49.9	5.6
G-C	0.58	80	17.9	40.4	50.1	6.0
G-D	0.58	60	19.3	42.2	52.3	5.8
G-E	0.58	60	16.6	40.6	48.1	5.4
B-Dust	0.72	70	9.3	25.8	35.5	-
B-A	0.67	70	11.8	30.4	41.7	5.3
B-B	0.67	80	12.9	31.3	43.7	5.5
B-C	0.67	62.5	13.0	33.1	42.7	5.4
B-D	0.67	47.5	13.2	35.2	45.6	5.6
L-Dust	0.61	60	18.5	38.0	50.2	-
L-A	0.55	90	18.0	44.3	55.7	6.6
L-B	0.55	70	21.2	47.8	58.0	6.7
L-C	0.55	82.5	22.7	46.2	56.2	6.1
L-D	0.55	65	21.4	46.9	56.6	6.0
S-Dust	0.75	80	8.2	23.3	31.3	-
S-A	0.67	85	12.7	34.5	41.4	5.2
S-B	0.67	75	14.9	31.4	43.3	5.6
S-C	0.67	97.5	14.7	32.8	42.8	5.5
S-D	0.67	75	12.1	30.5	39.9	5.2

Despite the presence of clay and the w/c ratio of 0.67, the basalt and sandstone concretes produced workable concretes with 28 day compressive strengths in the range of 39.9 to 43.7 N/mm<sup>2</sup>. Granite sand concretes at 28 days reached compressive strengths of 48.1 to 52.2 N/mm<sup>2</sup>. Limestone sand concretes yielded compressive strengths from 55.7 to 58.0 N/mm<sup>2</sup>, which is comparable to the dredged sand control mix with strength of 58.9 N/mm<sup>2</sup>. These results indicate that the shape of the manufactured sand positively affects the compressive strength of concrete as the limestone sands reach approximately the same strength as natural sand but with 0.07 higher w/c ratio. This provides encouraging evidence that at the same w/c ratio and with the addition of water reducing admixtures that the compressive strength of a manufactured sand concrete mix could easily surpass that of a natural sand mix.

## Conclusions

The sands produced with the V7 system had similar particle size distributions irrespective of the parent rock mineralogy. The shape and grading of the manufactured sands has been improved as demonstrated by the New Zealand flow cone results where all the manufactured sands fell within the prescribed standard envelope. The processing had reduced the amount of deleterious fines if they were present in the feed material as indicated by the methylene blue value and sand equivalence tests.

Workable concretes were produced from all manufactured sands, however higher water to cement ratios were required for the basalt and sandstone sands which contained clay to achieve the S2 slump. This in turn resulted in a reduction in the compressive strength. The limestone and granite sand concretes on the other hand yielded comparable compressive strengths to the natural sand control mix which had a lower water to cement ratio.

There was evidence that the incorporation of a water reducing admixture would allow manufactured sand concretes to surpass the compressive strength of the natural sand controls while maintaining adequate workability. Further work has since been performed to investigate this and the initial results from this study, which uses water reducing admixtures in manufactured sand concretes with fixed water to cement ratios, demonstrate that the manufactured sand compressive strength results for the four sands described in this paper exceed those of a natural sand mix at all testing ages. An overview of these results was presented at the Construction Materials Industry Conference (CMIC) [4] and the detailed results of this study will be published in 2013.

## Acknowledgements

The authors would like to acknowledge the financial and technical support of Kayasand Ltd., Aggregate Levy Fund for Wales project consortium, Kemco Ltd., Grace Construction Products, Aggregate Industries and Cemex.

## References

1. HARRISON, D J, WILSON, D, HENNEY, P J, HUDSON, J M. *Crushed Rock Sand In South Wales, A Reconnaissance Survey*. British Geological Survey Technical Report No. WF/00/0. 2000.
2. LUSTY, A. *Sand industry leads revival of Japanese aggregates*. Quarry, 2008/10, pp 90-92.
3. CEMENT CONCRETE & AGGREGATES AUSTRALIA. *Manufactured Sand National test methods and specification values*. Research report, 2007, pp 17-18
4. LUSTY, A, PILEGIS, M. *Sand Manufacturing from Quarry Surplus*, IQA-CCAA Construction Materials Industry Conference, Melbourne, Australia, September 2012.